

# Search for Muon to Electron Conversion at J-PARC

## - the COMET Experiment -

Satoshi MIHARA

KEK-IPNS/J-PARC Center/Sokendai


HQL2018, 28/May-1/June 2018 Yamagata

# Contents


- Introduction
  - Flavor physics with muons
- COMET Experiment at J-PARC
- Summary

# Flavor Physics

- Precise measurement of flavor structure
- Establishment of SM
- Indication of BSM?
  - muon g-2, proton radius, B leptonic decay ...





Branching Ratio UL



Bernstein & Cooper


# cLFV Searches using muon

- No sign of new physics from High Energy Frontier experiments so far
- Survey a large area in high energy region using forbidden process in SM with extremely large statistics
  - Role of Flavor Physics
- No SM background in muon LFV process
- Intense muon beam at high-power proton machines



# More Muons!

- Muons are produced from pion decays
- More muons produced in more pion decays
- Pion production yield depends on the power the proton driver
  - High-Power machine rather than High-Energy machine
- Proton current



# $\mu$ -e conversion search

- Atomic capture of  $\mu^-$

- Decay in orbit (DIO)

- electron gets recoil energy


- Capture by nucleus

- resultant nucleus is different

- $\tau_{\mu^N} < \tau_{\mu^{\text{free}}} \quad (\tau_{\mu^{\text{Al}}} = 860 \text{ nsec})$


- $E_{\mu e}(\text{Al}) \sim m_\mu - B_\mu = 105 \text{ MeV}$ 
  - $B_\mu$ : binding energy of the 1s muonic atom

- $\mu$ -e conversion**



Muon Decay In Orbit (39%)

nuclear muon capture (61%)




## $\mu$ -e conversion



# Experimental Techniques


- Process :  $\mu^- + (A, Z) \rightarrow e^- + (A, Z)$ 
  - A single mono-energetic electron
    - $E_{\mu e} \sim m_\mu - B_\mu$  : 105 MeV for Al
  - Delayed :  $\sim 1 \mu s$
  - No accidental backgrounds
- Physics backgrounds
  - Muon Decay in Orbit (DIO)
    - $E_e > 102.5 \text{ MeV}$  (BR:  $10^{-14}$ )
    - $E_e > 103.5 \text{ MeV}$  (BR:  $10^{-16}$ )
  - Beam Pion Capture
    - $\pi^- + (A, Z) \rightarrow (A, Z-1)^* \rightarrow \gamma + (A, Z-1)$
    - $\gamma \rightarrow e^+ e^-$

$$R_{\text{ext}} = \frac{\text{number of proton between pulses}}{\text{number of proton in a pulse}}$$



# Mu-e Conversion



## Electron Energy Spectrum



# Mu-e Conversion Search

## Experiments

- DeeMe
  - $\sim 10^{-13-14}$  using C or SiC for muonic atom formation
- COMET Phase-I & II
  - Al target to reach the  $10^{-14}$  sensitivity in Phase-I and  $10^{-16}$  in Phase-II
- Mu2e
  - Al target to reach the  $10^{-16}$  sensitivity





# J-PARC Facility (KEK/JAEA)

LINAC  
400 MeV

Rapid Cycle Synchrotron  
Energy : 3 GeV  
Repetition : 25 Hz  
Design Power : 1 MW

Main Ring  
Max Energy : 30 GeV  
Design Power for FX : 0.75 MW  
Expected Power for SX : > 0.1 MW

# J-PARC Facility (KEK/JAEA)

LINAC  
400 MeV

Neutrino beam to Kamioka

Material and Life  
Science Facility

R<sub>apid</sub> C<sub>ycle</sub> S<sub>ynchrotron</sub>  
Energy : 3 GeV  
Repetition : 25 Hz  
Design Power : 1 MW

M<sub>ain</sub> R<sub>ing</sub>  
Max Energy : 30 GeV  
Design Power for FX : 0.75 MW  
Expected Power for SX : > 0.1 MW

# J-PARC Facility (KEK/JAEA)

LINAC  
400 MeV

Neutrino beam to Kamioka

Material and Life  
Science Facility

Nuclear and Particle  
Physics Exp. Hall




R<sub>apid</sub> C<sub>ycle</sub> S<sub>ynchrotron</sub>  
Energy : 3 GeV  
Repetition : 25 Hz  
Design Power : 1 MW

M<sub>ain</sub> R<sub>ing</sub>  
Max Energy : 30 GeV  
Design Power for FX : 0.75 MW  
Expected Power for SX : > 0.1 MW

# COMET at J-PARC

- **Target S.E.S.  $2.6 \times 10^{-17}$**

- Pulsed proton beam at J-PARC
  - Insert empty buckets for necessary pulse-pulse width
  - bunched-slow extraction
- pion production target in a solenoid magnet
- Muon transport & electron momentum analysis using C-shape solenoids
  - smaller detector hit rate
  - need compensating vertical field
- Tracker and calorimeter to measure electrons
- Recently staging plan showed up. The collaboration is making an effort to start physics DAQ as early as possible under this.
  - **Phase-I 8GeV-3.2kW,  $< 10^{-14}$**
  - **Phase-II 8GeV-56kW,  $< 10^{-16}$**



# COMET Phase I & II

- 


## Phase I

- Beam background study, achieve an intermediate sensitivity of  $< 10^{-14}$

- 8GeV, 3.2kW, 150 days of DAQ


## Phase II

- 8GeV, 56kW, 1 year DAQ to achieve the COMET final goal of  $< 10^{-16}$  sensitivity





# COMET Phase-I Status



# COMET Primary Beamline






# Beamline








# Beamline









# Solenoid Magnet System




- Capture solenoid: Coil winding & cold mass assembly in progress. Cryostat design ongoing
- Transport solenoid: Installed and ready for cryogenic test
- Bridge & detector solenoids: design in progress.
- Cryogenic System: Refrigerator test completed. Helium transfer tube in production

# Phase-I Detector



Elec. trigger upgrade &  
Detail performance check



## Track Reconstruction



Hit selection & Hough Transformation



# Phase I Detector cont'd

Detector for beam BG measurement in Phase I and physics measurement in Phase II




LYSO Prototype



- LYSO cryostat production in progress
- Electronics design (almost) finalized




Phase I Ecal Design




Prototype straw tracker for performance evaluation



Epoxy resin



13 tubes broken out of 2700  
After two-years storage  
• Epoxy crystallization etc.



Final assembly design

# Other R&D


- Intensive studies of radiation hardness
- Aluminum muon stopping target design & X-ray monitoring
- New development of a proton beam monitor
- Cosmic-ray veto system
- Simulation and analysis tool development
- 8GeV acceleration & beam extinction factor measurement

# Other R&D


- Intensive studies of radiation hardness
- Aluminum muon stopping target design & X-ray monitoring
- New development of a proton beam monitor
- Cosmic-ray veto system
- Simulation and analysis tool development
- 8GeV acceleration & beam extinction factor measurement

# 8GeV Acceleration & Extraction


- 8GeV acceleration and extraction to the abort line (FX) and Hadron Hall (SX)
  - 4 bunches out of 9 bunches are filled with protons to realize the COMET beam time structure
    - Same number of protons per bunch with that of Phase I beam
  - Injection kicker timing is shifted to kick in only the filled bunch
  - SX with RF HV on to keep the bunched time structure



# $R_{ext}$ at the abort line (FX)




Extinction at MR Abort w/ FX (2018)




- Excellent extinction of  $10^{-12} \sim 10^{-11}$  is obtained = **Good enough for COMET !!**
- A strong dependence on beam condition (tune, beam loss) is observed.

# Rext in Hadron Hall (SX)


- Extracted pulsed proton beam injected to the Hadron Primary target and produced secondary beam transport to K1.8 area
- Secondary beam time structure measurement with a hodoscope
- Proton leakage is appeared in **K4\_rear only** within very early extraction timing (<0.1sec)
- No leakage is appeared in other region
- By rejecting <0.1sec events, upper limit of extinction is obtained: **<6.0 x 10<sup>-11</sup>**
- Good enough for COMET though we need further studies on K4\_rear leakage



w/o kicker shift = initial extinction



w/ kicker shift = improved extinction



# Summary

- Muon flavor physics experiment is a clue to investigate new physics BSM
- High-power proton driver to produce high-intensity muon beam
- COMET intends to improve the sensitivity to the mu-e conversion process by more than a factor of 10,000 in two steps;
  - Phase-I sensitivity  $< 10^{-14}$
  - Phase-II sensitivity  $< 10^{-16}$
- J-PARC MR operation at 8GeV to provide the proton beam
  - Proton beam extinction factor as good as  $6 \times 10^{-11}$  confirmed. Need further improvement in collaboration with the J-PARC accelerator group
- Pion/muon capture system, muon transport system as well as the physics detector in preparation
- Collaboration is expanding even now! Any young student and researcher is welcome to join the collaboration!!