



THE COMET EXPERIMENT

to Search for μ -e Conversion at J-PARC




A brief status report:

1. Introduction
2. Facility
3. Detectors
4. Closing

Kou Oishi
*Institute of Particle and Nuclear Studies (IPNS),
High Energy Accelerator Research Organization (KEK), Japan*

On behalf of the COMET Collaboration

Muon4Future 2025
Istituto Veneto di Scienze, Lettere ed Arti, Venice, Italy
28th May 2025



COMET


μ

e

INTRODUCTION




MUON-TO-ELECTRON CONVERSION



A charged lepton flavour-violating process

- ◆ Muon decays to single electron with no neutrino.
- ★ Strongly suppressed in the SM including the neutrino oscillation.
- ★ Branching ratio: $\text{BR}(\mu N \rightarrow e N) \sim \text{BR}(\mu \rightarrow e\gamma) < 10^{-54}$
- ◆ Reach up to $\sim 10^{-15}$ in several Beyond SMs.
- ★ Z' , leptoquarks, heavy right-handed neutrinos, SUSY-GUT, etc
- ◆ Model discrimination with $\mu \rightarrow e\gamma$ and $\mu \rightarrow eee$







EXPERIMENTAL PRINCIPLE

Signal & intrinsic BGs

- ◆ Signal: $\mu^- + N \rightarrow e^- + N$
 - ★ Monochromatic energy of **105 MeV** (Al)
- ◆ Intrinsic physics backgrounds: **decay-in-orbit (DIO)**
 - ★ Contaminate the signal region w/ a finite resolution.
 - ★ **Momentum resolution < 200 keV/c** is required.

Intense bunched muon beam

- ◆ World-class intensity proton beam @ J-PARC.
 - ★ To gain high statistics of muons.
 - ★ **An effective transport line from π to μ** is essential.
 - ★ Backgrounds arise from the proton and its secondaries.
 - ❖ Antiproton, radiative pion capture, muon decay in flight, etc...
- ◆ Bunched beam structure
 - ★ **Delayed timing window** for masking the beam BGs.
 - ★ The fraction of residual protons between the bunches (**extinction** = n/N in the right fig.) $< 10^{-10}$





COMET EXPERIMENT


Searching for μ -e conversion at J-PARC

- ♦ The final goal: $\mathcal{O}(10^{-17})$ sensitivity.
- ★ 10,000× improvement over the current limit.
- ♦ Dedicated facility and muon transport line being constructed.
- ♦ Two-staged plan: Phase-I and Phase-II



Phase-I

- ✓ Sensitivity $\mathcal{O}(10^{-15})$
- ✓ Physic measurement by cylindrical detectors 'CyDet'
- ✓ Beam & BG measurement by a tracker & calorimeter 'StrECAL'



Phase-II

- ✓ Sensitivity $\mathcal{O}(10^{-17})$
- ✓ Physic measurement by StrECAL






PHASE-I

Sensitivity $\mathcal{O}(10^{-15})$

- ◆ $\pi \rightarrow \mu$ in the transport solenoid.
- ◆ **CyDet** combining with the muon stopping targets,
 - ★ **CDC**: Cylindrical Drift Chamber (momentum)
 - ★ **CTH**: Cylindrical Trigger Hodoscope (time and trigger)
- ◆ Cosmic Ray Veto surrounding the CyDet

Beam profile & beam-related BGs

- ◆ Measured by the Phase-II detector: StrECAL.






PHASE-II


Sensitivity $\mathcal{O}(10^{-17})$

- ♦ The transport line will be extended.
- ♦ The additional electron spectrometer further suppresses low momentum electrons and beam BGs.
- ♦ **StrECAL** combining
 - ★ **Straw Tube Tracker** (momentum)
 - ★ **ECAL**: Electromagnetic calorimeter (energy & time)
 - ❖ Provides trigger signals.






COMET COLLABORATION



Our Collaborators

with the delivered solenoid magnet



COMET

μ

e




FACILITY



PROTON BEAM

J-PARC Proton Beam for COMET

- ♦ Accelerated up to 8 GeV
 - ★ (1) To minimise antiprotons.
 - ★ (2) '**Extinction**' $< 10^{-10}$
 - ❖ The fraction of residual protons
- ♦ 3.2 (56) kW for Phase-I (Phase-II)
- ♦ Bunched slow extraction for the timing-window measurement
 - ★ 4 out of 9 buckets will be filled.



The measured extinction is $< 1.0 \times 10^{-10}$

- ♦ @ K1.8BR of the Hadron Facility (T78 exp. in 2021)


No inter-bunch contaminations in T78 exp.





COMET PROTON BEAM LINE

COMET Beam Line (C-Line)

- ◆ Dedicated beam line for COMET
- ◆ Proton beam monitors are being developed.
- ★ Diamond, TiO_2 , and SiC: High radiation tolerance
- ◆ **Commissioning of the 8 GeV slow extraction succeeded.**
- ★ COMET Phase-a (later)



The C-Line branching point








PION PRODUCTION SECTION

Proton Target

- ◆ Graphite (Tungsten) for Phase-I (II).

Pion capture solenoid

- ◆ 4.4 T superconducting magnet
- ◆ Pions extracted in the backward direction.
 - ★ Better exclusive collection of low-momentum pions
- ◆ Delivered and installed in 2024!







MUON TRANSPORT SOLENOID


Characteristic 90°-bent solenoid

- ◆ The helical trajectories centre drifts vertically.
 - ★ Additional dipole magnetic field for compensation
 - ★ Charge and momentum selection with optimum collimators.
- ◆ The magnet and beam collimator are designed to select the target low-momentum μ^- .
 - ★ μ^- of 30–50 MeV/c tend to stop in the aluminium target.



Vertical positions of different particle types before the collimator

Red : p, e^+, π^+, μ^+ , Blue: e^-, π^-, μ^- ,
 Orange : $p, e^+, \pi^+, \mu^+, e^-, \pi^-, \mu^-$
 Magenta: μ^- ($p > 70$ MeV/c), Black : π^- ,
 Cyan: e^- ($p > 100$ MeV/c), Green : Stopped μ^-






MUON STOPPING TARGET

Aluminium Target


- ◆ 17 aluminium discs
 - ★ 10 cm radius, 200 μ m thickness, and 50 mm spacing.
 - ★ Stability and performance tests of various aluminium alloys are ongoing.
- ◆ 4.7×10^{-4} stopping muons / proton for Phase-I

Germanium Detector


- ◆ To be placed to measure muonic X-rays for normalisation.



Prototype of the target and support



Test production with different aluminium alloys










PHASE-a

The 1st Commissioning of the COMET facility in 2023

- ◆ Proton Beam
 - ★ Slow-extracted pulsed 8 GeV proton beam at 260 W ($\sim 1/10$ of Phase-I)
 - ★ Beam tuning and profile measurement were well performed.
- ◆ The muon beam was successfully transported by the TS.
 - ★ Muon momentum spectrum was measured for the first time!





COMET


DETECTORS



CYLINDRICAL DRIFT CHAMBER

Requirements

- ◆ Measure signal electrons' momentum avoiding beam particles.
- ◆ Spatial resolution $< 200 \mu\text{m}$









Design

- ◆ ~ 5000 (Au plated W) sense wires in 20 layers
 - ★ Stereo wire configuration for **3-dimensional position measurement**
- ◆ Chamber radius: 496 mm to 840 mm
 - ★ Suppress hits by DIO electrons $< 60 \text{ MeV}/c$
- ◆ Gas: **He : iso-C₄H₁₀ = 90:10**

CDC Construction completed in 2016

- ◆ Commissioning ongoing
 - ★ Performance evaluation with cosmic rays
 - ★ Chain test of the front- and back-ends electronics including the trigger system.









CYLINDRICAL TRIGGER HODOSCOPE

Requirements



- ◆ (Primary) trigger decision
- ◆ T_0 measurement for tracking

Design

- ◆ 2×64 plastic scintillators installed at each end
 - ★ Thickness: (inner) 5 mm (outer) 10 mm
 - ★ Readout by MPPCs through a plastic fibre bundle.
 - ★ > 40 p.e. for a detection efficiency > 99%
- ◆ MPPCs operated $< -36^\circ\text{C}$
 - ★ Against radiation damage.
- ◆ For reasonable trigger rate,
 - ★ 4-fold coincidence
 - ★ Inner lead shield to block gamma rays from inside.
- ◆ Front-end electronics being produced
- ◆ Mass production will start.



Lateral view




Frontend electronics



TRIGGER SYSTEM

Trigger electronics


- ♦ FC7: the central trigger-administrating electronics
 - ★ **FC7**: general use FPGA board supporting gigabit data transfer (developed by CMS@CERN).
 - ★ Both the CyDet and StrECAL system share it.
- ♦ COTTRI: Frontend digitiser & trigger boards for CyDet
 - ★ Online waveform processing with flash ADC chips.



Trigger scheme

- ♦ CyDet trigger is being developed to achieve a trigger rate $< \sim 20$ kcps.
- ♦ Machine learning-based trigger logic on FPGA
 - ★ Boosted decision tree for hit classification
 - ★ Neural network for online tracking
- ♦ Software trigger is getting attractive.

CyDet trigger system







COSMIC RAY VETO

Requirements

- ◆ Detection efficiency $> 99.99\%$
- ★ CR is one of the most crucial BG sources.



Top and side CRV module

Design


- ◆ Top&side: **plastic scintillating stripes**
 - ★ 4 layers on each side
 - ★ readout by MPPCs through wavelength-shifting fibres
- ◆ Front&back: **Resistive Plate Chamber strips**
 - ★ A module with 2D-aligned RPC strips
 - ★ 5 to 7 layers on each side



1st Module being commissioned

1st module of the lateral CRV modules

- ◆ Being commissioned with cosmic rays to evaluate the detection efficiency



RPC module






STRAW TUBE TRACKER

Requirements

- ♦ Momentum resolution $< 200 \text{ keV}/c$
 - ★ Operation in a vacuum of $< 100 \text{ Pa}$

Thin-wall straw tube

- ♦ 9.75 mm Φ straw with 20 μm thickness
 - ★ Ultrasonic welding for less material budget.
 - ★ 5 mm Φ with 12 μm in Phase-II
- ♦ **Ar:C₂H₆ = 50:50**
- ♦ A prototype test showed a **spatial resolution of $\sim 110 \mu\text{m}$** .
 - ★ Momentum resolution $< 200 \text{ keV}$ is achievable.
 - ★ Succeeded operation in vacuum of $< 0.1 \text{ Pa}$.
- ♦ The 1st station was commissioned in Phase-a.
 - ★ The 2nd and 3rd stations are being constructed.



1st Straw Station in Phase-a



ECAL

Requirements

- ◆ Particle identification for the beam measurement.
- ◆ Energy resolution $< 5\%$ to suppress trigger rate of DIO electrons.

LYSO Crystal Scintillators






- ◆ High density (7.1 g/cm^3), high light yield (70% NaI), and fast time response (40 nsec)
- ◆ Dimension of $2 \times 2 \times 12 \text{ cm}^3$.
- ◆ Readout by $10 \times 10 \text{ mm}^2$ APD + FE electronics
- ◆ ~ 2000 crystals ($\sim 1 \text{ m}^2$ sensitive area.)

Prototype w/ 8×8 crystals

- ◆ Good performance at 105 MeV/c
 - ★ **Energy resolution of 3.9%**
 - ★ **Position resolution of 7.7 mm**
 - ★ **Timing resolution of 0.5 nsec**

Detector construction beginning

- ◆ Quality control of the crystal modules construction





COMET

μ

e

CLOSING



PHASE-I SENSITIVITY

Single Event Sensitivity (SES)

- ♦ Estimated 3×10^{-15} for 150 days operation.

$$B(\mu^- + \text{Al} \rightarrow e^- + \text{Al}) = \frac{1}{N_\mu \cdot f_{\text{cap}} \cdot f_{\text{gnd}} \cdot A_{\mu-e}} = 3 \times 10^{-15} \text{ (as SES)}$$

- ★ $N_\mu = 1.5 \times 10^{16}$: the number of muons stopped in the target
- ★ $f_{\text{cap}} = 0.61$: the fraction of captured muons to total muons on target
- ★ $f_{\text{gnd}} = 0.9$: the fraction of μ -e conversion to the ground state in the final state
- ★ $A_{\mu-e} = 0.041$: the net acceptance for the μ -e conversion signal (see below)

Physics Backgrounds

- ♦ "Prompt beam" and "delayed beam" components will be directly evaluated.

Event selection	Value
Online event selection efficiency	0.9
DAQ efficiency	0.9
Track finding efficiency	0.99
Geometrical acceptance + Track quality cuts	0.18
Momentum window (ε_{mom})	0.93
Timing window ($\varepsilon_{\text{time}}$)	0.3
Total	0.041

Physics background sources

Type	Background	Estimated events
Physics	Muon decay in orbit	0.01
	Radiative muon capture	0.0019
	Neutron emission after muon capture	< 0.001
	Charged particle emission after muon capture	< 0.001
Prompt Beam	* Beam electrons	
	* Muon decay in flight	
	* Pion decay in flight	
	* Other beam particles	
	All (*) Combined	≤ 0.0038
	Radiative pion capture	0.0028
	Neutrons	$\sim 10^{-9}$
Delayed Beam	Beam electrons	~ 0
	Muon decay in flight	~ 0
	Pion decay in flight	~ 0
	Radiative pion capture	~ 0
	Anti-proton induced backgrounds	0.0012
Others	Cosmic rays [†]	< 0.01
Total		0.032

[†] This estimate is currently limited by computing resources.



SUMMARY & SCHEDULE

COMET experiment will search for μ -e conversion at J-PARC.

- ◆ Aims at single event sensitivity: 3×10^{-15} (Phase-I) and $O(10^{-17})$ (Phase-II).
- ◆ Perform a direct measurement of the beam profile and backgrounds in Phase-I.
- ◆ The facility & beam line construction is getting completed.
- ◆ The detector construction is also progressing.
 - ★ CyDet, StrECAL, and Cosmic Ray Veto
- ◆ We will start with low-intensity ($\sim 10\%$ power) commissioning & data taking runs.

